

SPC-FODS.DWG

RELEAS	>	1973 A	
DESCRIP	REV	DCP # REV	WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC
REVISIONS			ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION.

DESCRIPTION RELEASED

DRAWN S

CHECKD DATE APPRVD DATE

2/12/07 DATE

JN 04/26/08


둗


04/28/08


DOC. NO. SPC-FD05 * Effective: 7/8/02 * DCP No. 1398

SPC Type	SPC21902	SPC21903	SPC21904	SPC21905	SPC21906	SPC21907	SPC21908	SPC21909	SPC21910	SPC21911	SPC21912	SPC21913	SPC21914	SPC21915	SPC21916	SPC21917	SPC21918	SPC21919	SPC21920	SPC21921	SPC21922	SPC21923	SPC21924	SPC21925	SPC21926	SPC21927	SPC21928
Length (East)			1 + 0 นี้							3 + 1"							5 + 1 <u>"</u>							7±1"			
Color	Black	Blue	Green	Red	Yellow	White	Black	Blue	Green	Orange	Red	Yellow	White	Black	Blue	Green	Orange	Red	Yellow	White	Black	Blue	Green	Orange	Red	Yellow	White
SPC Typ	SPC2192	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2193	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2194	SPC2195	SPC2195	SPC2195	SPC2195	SPC2195	SPC2195

SPC21955	SPC21954	SPC21953	SPC21952	SPC21951	SPC21950	SPC21949	SPC21948	SPC21947	SPC21946	SPC21945	SPC21944	SPC21943	SPC21942	SPC21941	SPC21940	SPC21939	SPC21938	SPC21937	SPC21936	SPC21935	SPC21934	SPC21933	SPC21932	SPC21931	SPC21930	SPC21929	No.	SPC Type
			50 ± 4"						\ - 	ンF + ン"						14 ±1.5"							10 ± 1.5"				(Feet)	Length
White	Yellow	Red	Orange	Green	Blue	Black	White	Yellow	Red	Green	Blue	Black	White	Yellow	Red	Orange	Green	Blue	Black	White	Yellow	Red	Orange	Green	Blue	Black	COLO	2







	占	_	2	3	6	4	5	7	D0
WIRE CONNECTION TABLE	WIRE COLOR	WHITE /OR ANGE	ORANGE	WHITE /GREEN	GREEN	BLUE	WHITE/BLUE	WHITE/BROWN	BROWN
N TABLE		PAIR	TWISTED	PAIR	TWISTED	PAIR	DALSIML	PAIR	TWISTED
	J2	1	2	3	6	4	5	7	D0

6.02







				7
	DESCRIPTION	Q'TY	ITEM	Į,
	COLOR: SEE TABLE, FREQUENCY: 350MHZ			
,	TIA/EIA 568-B.Z CAT.5E PATCH CORD UTP		UTP LAN CABLE	
♂;	24AWG CSA 219561 CMG FT4 ETL VERIFIED	1PC		<u> </u>
ð	DARLE MARKING: FOARO33 (III) OM 75"O AF		,	П
	#24X4P+JACKET: PVC, 0.0=\$5.3±0.1MM			
	WITH "GOC" MARKING			
	INSERT BAR: UL94V-2, COLOR: NATURAL			
	COLOR: NATURAL		MODULAR PLUG	_
	2SET INSULATOR: POLYCARBONATE, UL94V-2	2SET	RJ-45 8P8C	2
	15u", GOLD PLATED			
	CONTACT: COPPER ALLOY			

שחחטכ	ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED ALL STATEMENTS AND TECHNICAL INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL. THE CONDITIONS OF USE ARE BEYOND OUR CONTROL. THE LUSER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LABILITY WHATSOEVER IN CONNECTION THEREWITH.
-	

		i		ASE SEE		MININED					
	PURPOSES ONLY. APPROVED BY: Jason Nash			ISE							
				Jason Nash	CHECKED BY:	Dan McVicker	DRAWN BY:				
	04/28/08	DAIE:	7	04/28/08	DATE:	2/12/07	DATE:	No.			
	DATE: CALE: NTS U.O.M.: Millimeters SHEET: 1 OF			<u>⊳</u>	DATE: SIZE DWG. NO.		DRAWING TITLE:	ITEM			
					DWG. NO.	0		Q"TY			
				TA-816		Cat Se Patch Cords, No		DESCRIPTION			
				TA-816-dwg / /	ELECTRONIC FILE	Non-Molded		Ž			
) 1			>	REV						